



Safe 'n' Silent™ Pro



General Product Information

ROCKWOOL stone wool products are made of basalt, a volcanic stone.

ROCKWOOL stone wool products are non-combustible with a melting point approximately 1000°C. They are particularly suitable for thermal insulation, fire protection and sound reduction or absorption.

ROCKWOOL stone wool is inorganic and contains no nutritious substance. Therefore it will not be attacked by microorganisms. Stone wool will not rot and does not attract vermin.

No CFCs, HFCs, HCFCs, or asbestos are used in the manufacture of ROCKWOOL stone wool products.

Applications

ROCKWOOL Safe 'n' Silent Pro is designed and manufactured to achieve excellent acoustic insulation performance in all types of drywall partition configurations as well as for concrete soffit application. It is recommended to be used for drywall partition applications in hospitals, cinemas, schools, offices, residential and industrial buildings.

Selected products in the Safe 'n' Silent Pro range are recommended for application in building condensation control of concrete soffit where there are noticeable temperature differences on each side. An example for this would be in car parks and buildings with air conditioned server room, data

centre or cold storage facilities.

Safe 'n' Silent Pro meets the requirements of Noise Criteria (NC) specifications developed by the ROCKWOOL company. NC comprehensively measures the noise levels of a room and with the use of NC ratings, recommends the desired acoustic comfort level of a room/space.

It also has a thermal conductivity (k value) of 0.034 W/mK, according to ASTM C518 standard test method.

Facings

Optional facing with one or two sided glass tissue is available upon request for perforated wall panel. A variety of facing options are available for application in concrete soffit.

For more information, please contact your local representatives.

Packaging and storage

ROCKWOOL Safe 'n' Silent Pro is shrink-wrapped in polyethylene sheets for ease of handling, transportation, storage and identification.

Products should be stored indoors or under waterproof covering.

Technical Parameters

Product Name	Safe 'n' Silent Pro 330	Standards
Noise Absorption Co-efficient at 50mm (NRC)	0.90	EN ISO 354 / ASTM C 423-01
Fire Performance	Non-combustible / A1 Fire Classification	EN13501-1
Melting Point	More than 1000°C	ASTM E794
*Thermal Conductivity 20°C λ Value (W/mK)	0.036	ASTM C518
R-value at 50mm thickness thickness (m ² K/W) Water	1.389	
Water Absorption (partial immersion)	1.0kg/m ²	EN1609.97
Water Vapor Absorption	Less than 0.04 Vol %	ASTM C1104/ C1104M
Thickness	50mm	EN822
Applications	Recommended for commercial applications such as retail and office partition walls	

* Thermal conductivity values are based on testing conducted in external accredited laboratory in accordance to ASTM C518 : 1991.

Test reports are available upon request. For design, it is recommended to use a safety factor of 20% as design value.



G00085
G00094
G00095
SGBP 2018-1622



SGBP 2018-1897
SGBP 2018-1898



*Note: EUCEB only applicable for products produced in India & Malaysian factories

Disclaimer: The information contained in this data sheet is believed to be correct at the date of publication. ROCKWOOL does not accept responsibility for the consequences of using Safe 'n' Silent Pro in applications different from those described above.

**Indonesia Representative Office
Malaysia Sdn Bhd**
Wisma Pondok Indah Tower 3
17th Floor, Jl. Sultan Iskandar Muda V
Jakarta 12310, Indonesia
T (+62) 21 2965 8071

ROCKWOOL Malaysia Sdn Bhd
Lot 4, Solok Waja 1
Bukit Raja Industrial Estate
41050 Klang, Selangor, Malaysia
T (+60) 3 3341 3244

**ROCKWOOL Building Materials
(Singapore) Pte. Ltd.**
No 7, Tuas Avenue 1, Jurong Town,
Singapore 639492
T (+65) 6861 5722

www.rockwool.com